



日照瑞科特工贸有限公司 扣件检测报告



(Rizhao) RRICOM INDUSTRIAL CO.,LIMITED---Coupler Test Report

编号 Number: 20170517

检验类别 Category: () 过程检 Process inspection (√) 出货检 Shipment inspection
 检验日期 (Inspect date): 2017. 5. 17

Order Number 订单号	RSC20170517	Qty. Order 订单数量	10000 pcs	Surface 表面处理	High Quality Galvanized
Part name 产品名称	Drop Forged Double (Fixed) Coupler	Material 材料	High Quality Q235 Steel	Checker	Haorong Ma
Qty. Inspect 抽检数量	8	Packing measure 包装方式	Steel Pallet and Woven Bags with membrane	检验员	

检测项目 Test Items	抽样 (Sample)	S1	S2	S3	S4	S5	S6	S7	S8
--------------------	-------------	----	----	----	----	----	----	----	----

产品外观 Inspection for production	1、产品字标 Logo	EN74							
	2、标准件配置 Standard configuration	1/2*87 螺栓螺母垫片 (Bolt)							
	3、螺栓长度 Length of the bolt	87mm	87mm	87mm	87mm	87mm	87mm	87mm	87mm
	4、螺母对边 Opposite side of the nut	21mm	21mm	21mm	21mm	21mm	21mm	21mm	21mm
	5、扣盖打开角度 Angle of opening plate	95	95	90	90	95	95	90	95
	6、规格 specification	48.3mm	48.3mm	48.3mm	48.3mm	48.3mm	48.3mm	48.3mm	48.3mm
	7、重量 Weight	1.03kg	0.99kg	1.02kg	1.01kg	1.01kg	1.00kg	0.99kg	0.99kg
	8、中心轴铆钉间隙 central rivet space	/	/	/	/	/	/	/	/
螺栓、螺母检验 inspection for bolts and nuts	螺栓预紧力=100nm The pre-tightening force of the bolts	Ok	Ok	Ok	Ok	Ok	Ok	Ok	Ok

防滑 Anti skid	The pre-tightening force of the bolts 螺栓上紧力=50nm					
	P=5kn	P=10kn	P=15kn	P=20kn	P=25kn	单位 (mm)
	0.00	0.2	0.3	/	/	

破坏 Damage	The pre-tightening force of the bolts 螺栓上紧力=50kn				
	P=20kn	P=30kn	P=35kn	P= / kn	备注 Remarks
	ok	ok	ok	Damaged	

参照标准 Standard: EN74

检验意见 Advice: 下滑力 P=15kn 时, 下滑距离为 0.3mm; 破坏力 p=30kn 时, 扣件不破坏。

检验结论 Results: 合格 (ok)

(检验章)
 2017年5月17日
 核可 (Approved by): Guohui Sun
 2017.5.17